

VarioCAM[®] HD head security

Infrared Thermal Imaging System for Security and Monitoring Tasks



- 1) Vehicle-based surveillance
- 2) Monitoring of a parking lot

INFRA^{TEC}.

Europe's leading specialist for infrared sensors and measurement technology

Uncooled detector with up to (1,024 × 768) IR pixels

Opto-mechanical MicroScan with up to (2,048 × 1,536) IR pixels

Spectral range (7.5 ... 14) μm

Personnel detection range 6.1 km

Vehicle detection range 10.7 km

Solid light metal housing (IP67)

No US export license required



www.InfraTec.eu

Made in Germany



Spectral range	(7.5 ... 14) μm
Detector	Uncooled Microbolometer Focal Plane Array
Detector format (IR pixels)	(1,024 × 768), with built-in opto-mechanical MicroScan unit (2,048 × 1,536)* (640 × 480), with built-in opto-mechanical MicroScan unit (1,280 × 960)*
Temperature measuring range	(-40 ... 2,000) °C*
Measurement accuracy	± 1 °C or ± 1 %*
Temperature resolution @ 30 °C	Up to 0,02 K*
Frame rate	Full-frame: 30 Hz (1,024 × 768), sub-frame formats*: 60 Hz (640 × 480) / 120 Hz (384 × 288) / 240 Hz (1,024 × 96) Full-frame: 60 Hz (640 × 480), sub-frame formats*: 120 Hz (384 × 288) / 240 Hz (640 × 120)
Storage media	SDHC Card, external control computer for camera control and data acquisition*
Image storage	Time-, trigger- and temperature controlled recording of 16 bit single frames or image sequences with timestamp, video streaming in MPEG format
Realtime storage*	Computer-aided storage of radiometric sequences by GigE interface with up to 240 Hz
Lens mount	Bayonet to comfortably switch objectives, automatic objective detection and data transfer; screw-on interface*
Focus	Motor-driven, automatic or manual, accurately adjustable
Zoom	Up to 32× digital, stepless
Personnel detection range	Up to 6.1 km
Vehicle detection range	Up to 10.7 km
Dynamic range	16 bit
Interfaces; Trigger*	GigE Vision*, DVI-D (HDMI), C-Video, RS232, USB 2.0, WLAN*; 2 × digital I/O, 2 × analogue I/O
Tripod adapter	1/4" photo thread
Power supply	AC adapter, (12 ... 24) V DC, PoE*
Storage and operation temperature	(-40 ... 70) °C, (-25 ... 55) °C
Protection degree	IP54, IEC 60529, IP67 with screw-on interface*
Impact strength; vibration resistance in operation	25 G (IEC 68 - 2 - 29); 2 G (IEC 68 - 2 - 6)
Dimensions; weight	(221 × 90 × 94) mm; 1.15 kg (basic configuration with standard lens)
Further functions	Camera internal emissivity correction, shutter free operation, use of various colour sets, contrast enhancement, user profile, language selection
Analysis and evaluation software*	IRBIS® 3, IRBIS® 3 report, IRBIS® 3 view, IRBIS® 3 plus*, IRBIS® 3 professional*, IRBIS® 3 remote HD, IRBIS® 3 control*, IRBIS® 3 online*, IRBIS® 3 process*, IRBIS® 3 active*, IRBIS® 3 mosaic*, IRBIS® 3 vision*

* Depending on model

The **thermographic high-resolution system VarioCAM® HD head security** was conceived for demanding monitoring and measurement tasks in stationary or vehicle-mounted operation. Images with resolutions of up to 3.1 Megapixels can be taken in combination with the integrated MicroScan feature, which was designed for continuous operation. The VarioCAM® HD head security generates **brilliant 16-bit thermographic images of highest quality** and offers unprecedented measurement ranges and efficiency, especially during **day and night detection and identification of distant persons and vehicles**.

The **various sets of equipment** make it easy to adjust the setup to the respective measurement task: The application range includes automatic threshold recognition and signalling up to digital realtime image acquisition via Gigabit-Ethernet. The **all-weather light metal housing (IP67)** allows **trouble-free and inexpensive operation** under harsh weather conditions.

The **big standard temperature range**, a complete optical assortment as well as the extensive equipment and the **powerful IRBIS® 3 software** for thermographic data acquisition and evaluation make the VarioCAM® HD head security an **ideal tool for monitoring and investigation**. With the application-specific configuration, this stationary thermographic system is even suited for tasks, which require continuous and automatic operation.

Application examples:

- Remote sensing and monitoring
- Integration in system solutions for ground vehicles, helicopters and maritime applications
- Undercover investigations from greater distances
- Stationary protection of critical infrastructure

Detector format (IR pixels)		(640 × 480)	(1,024 × 768)
Lens	Focal length (mm)	FOV (°)	FOV (°)
Super wide-angle lens	7.5	(93.7 × 77.3)	(98.5 × 82.1)
Wide-angle lens	15	(56.1 × 43.6)	(60.3 × 47.0)
Standard lens	30	(29.9 × 22.6)	(32.4 × 24.6)
Telephoto lens	60	(15.2 × 11.4)	(16.5 × 12.4)
Telephoto lens	120	(7.6 × 5.7)	(8.3 × 6.2)

Headquarters

InfraTec GmbH
Infrarotsensorik und Messtechnik
 Gostritzer Str. 61 – 63
 01217 Dresden / GERMANY
 Phone +49 351 871-8630
 Fax +49 351 871-8727
 E-mail thermo@InfraTec.de

USA office

InfraTec infrared LLC
 5048 Tennyson Pkwy.
 Plano TX 75024 / USA
 Phone +1 844-226-3722 (toll free)
 E-mail thermo@InfraTec-infrared.com